



## MOUNTING SUGGESTIONS:

**Honda**  
**Gold Wing GL1800 2001-2011**  
**without OEM heat - One-piece**

**Hardware:** Stock side Allen bolts x 4

**Tools needed:** Metric Allen wrenches

**Note:** These instructions are for installing Mustang seats 79900 and 79907 on GL1800 models **without** OEM heat. If your model has OEM heat, please refer to the instructions for 79902 and 79909.

The rear seat heaters on Mustang seat 79907 will **not** function properly without also installing passenger backrest 79908.

### Removal of Stock Seat:

1. Remove the grab rails from the motorcycle by removing the two Allen bolts.
2. Lift the stock seat up and back to remove from motorcycle.



## Installation of Mustang Seat:

**Please read ALL instructions before installing seat!**

79907:

1. Open the battery box and disconnect the battery, and remove the cover to the fuse box.
2. Check to see the seat's electric cables are free of kinks and folds. Check both switches for ease of operation. **Note:** top position is high, center position is off, bottom position is low.
3. Run the seat cables **under** the frame rail to the fuse box and battery.
4. Secure the purple wire with the small ring terminal to the top terminal in the fuse box.
5. Secure the black wire with large ring terminal and in-line fuse to the **positive** battery terminal.
6. Secure the black wire with large ring terminal and **no** in-line fuse to the **negative** battery terminal.



7. Plug the cable from passenger backrest 79908 into the pigtail of the rear seat heater.

8. Check to be sure all wires are routed and connected properly, then close the fuse box and re-connect the battery.

*79900 and 79907:*

1. Holding the back of the seat up against the passenger backrest, slide the nose bracket under the frame's receiver. If the side panels seem to interfere with install, slide the seat back until the nose of the seat drops below the side covers, then push forward.

2. Align the grab rails to the seat, slide the stock Allen bolts through the grab rails and the seat, and into the frame mounting bosses.

3. Tighten the four Allen bolts securely.

**Enjoy the comfort and custom look of your new Mustang seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 79900, 79907

**You are cordially invited to**  
**— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.