



MOUNTING SUGGESTIONS:

Yamaha
Virago 700/750/1000/1100
2008-2015 - One-piece Seat

| | |
|----------------------|-----------------------|
| Hardware: | Stock Allen bolts |
| Tools needed: | Metric Allen wrenches |

Note: This seat will not fit Virago 250 or 535 models.

Removal of stock seat:

1. Remove the side covers. Locate and remove the two Allen bolts from each side of the nose of the seat.
2. Lift the nose of the seat and slide the seat forward to remove the seat from the frame.



Installation of Mustang seat:

Note: Be extremely careful to keep the seat's front mounting bracket from contacting the fuel tank to avoid scratching the tank.

1. Align the rear tab of the Mustang seat with the rearward mounting bracket on the fender, and push seat back fully to engage. A solid chop to the seat may be required to seat it fully back.
2. Align the front mounting brackets with the mounting holes in the frame and re-install the stock Allen screws.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75240, 75244

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.