Mounting Suggestions
Harley-Davidson® FXR 1982-94 & 1999-00 One-Piece Seat

Tools Required:
- SAE Sockets
- SAE Open-End Wrenches
- Small Screwdriver

Hardware:
- OEM Hinge & Latch System (Stock)
- Fender Bolts & Washers (Stock)
- Fender Screw (Stock)
- Mustang Nose Bracket #75080 (Optional- Sold Separately)

Baseplate Features:
Mustang one-piece FXR seats can be used on any 982-94 and1999-00 models. The formed steel baseplate has a nose tab as well as mounts for the stock hinge and latch. Rubber bumpers help isolate vibration and carpet base protects the fender. If the hinge and latch are not used, Mustang's Nose Bracket,Part #75080, is required to engage to the nose tab of the one-piece seat.

Stock One-Piece Seat Removal Steps

1. Remove rear fender screw located at back of seat and set aside. The rear fender screw will be used to attach the passenger seat of your new Mustang One-Piece Seat.
2. Slide one-piece seat back and up to remove.

Stock Two-Piece Seat Removal Steps

1. Unlatch solo seat to expose the hinge.
2. Push plastic retaining clip of hinge with small screwdriver or fingers.
3. Slide solo seat back to clear hinge and remove.
4. Unbolt the OEM hinge and latch from the bottom of the solo seat and set aside. The OEM hinge and latch will be used on your new Mustang One-Piece Seat.

Stock Passenger Seat Removal Steps

1. Remove rear fender screw located at back of seat and set aside. The rear fender screw will be used to attach your new Mustang One-Piece Seat.
2. Loosen front mounting bolts.
3. Slide passenger seat back and up to remove.

Mounting Suggestions: Harley-Davidson® FXR 1982-94 & 1999-00 One-Piece Seat continued from page 1)

Mounting of Mustang Seat- Seat & Nose Bracket Option

1. Bolt Mustang Nose Bracket, Part #75080 (sold separately), to rear mounting holes on the fuel tank.
2. Engage nose tab into the nose bracket.
3. Secure one-piece seat with stock rear fender screw

Mounting of Mustang Seat- OEM Hinge and Latch Option

1. Mount OEM hinge and latch system to bottom of Mustang one-piece seat.
2. Secure one-piece seat with stock fender screw

Enjoy the Comfort of your new Mustang Seat!

These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75158, 75445, 75313, 75743, 75305, 75505, 75736