Mounting Suggestions for the Kawasaki Vulcan 800 1995-2005 and Vulcan 800 Classic 1996-2005 Solo Only

Tools Required:
- Metric Allen Wrenches
- Metric Sockets

Hardware:
- Stock Bracket Bolts
- Two Nylon Washer (Included)

Baseplate Features:
The solo has a marine-grade fiberglass baseplate that is a direct replacement for the stock seat. Rubber bumpers are positioned to protect the frame and fender.

Stock Seat Removal Steps

1. Remove rear 6 mm bolt.
2. Slide seat back and up to remove. The seat may be tight and some force is necessary.
3. Remove center bracket from fender. The two bolts will be used to install your new Mustang Solo.

Mounting of Mustang Seat

1. Engage nose tab of Solo.
2. Place one nylon washer between each chrome solo bracket and fender.
3. Secure rear of solo with the stock bolts.

Enjoy the comfort of your new Mustang Seat!

These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref part #75935, 75937