



## MOUNTING SUGGESTIONS:

### Harley-Davidson® FL "Air Ride" style 1983-2018 Solo Seat

**Hardware:**  $\frac{5}{16}$ "-18 serrated nuts x 3

**Tools needed:**  $\frac{1}{2}$ " open-end wrench

#### Removal of stock seat:

1. Pivot seat up to reveal mounting bolts and unscrew the bolts from the seat. These will not be used to mount your Mustang solo.
2. Remove stock seat from the pivoting bracket.



#### Installation of Mustang seat:

**Note:** The pivoting bracket has changed through the years, but the Mustang solo will fit all versions.

1. Remove the three hex nuts from the studs on the bottom of the Mustang solo.
2. Position Mustang solo onto pivoting bracket and align the three studs with the holes in the bracket.
3. Install the three hex nuts onto the studs and tighten securely.
4. Pivot seat into riding position.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76455, 76456, 79548, 79549

**You are cordially invited to  
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.