



MOUNTING SUGGESTIONS:

Honda Fury 2010-2018 Passenger Seat

Hardware:	6mm x 25mm hex bolt x 2 Chrome spool washer x 2 ¼" Chrome washer White nylon washer 6mm x 15mm Allen screw
Tools needed:	Metric Allen wrenches 10mm wrench

Note: See solo instructions for removing stock seat. Mustang passenger seat will *not* work with stock solo.

Mounting of Mustang seat:

1. Insert the solo's front bracket into the frame receptacle behind the fuel tank above the shock mount.
2. Place the two white nylon washers under the solo brackets, the two spool washers over the seat brackets, and secure to fender using the 6mm x 25mm hex bolts.
3. Align the slotted brackets on the passenger seat with the spool washers and slide seat fully forward.
4. Place white nylon washer under rear passenger seat bracket and secure to fender with a 6mm x 15mm Allen screw.

Passenger Backrest (if applicable):

1. The passenger backrest can be set forward or back with the $\frac{5}{16}$ "-24 x 1" adjustment screw.
2. The height of the passenger backrest can be set by tightening the rear knob to engage one of the notches on the post.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76281, 76283, 79627, 79629

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.