



MOUNTING SUGGESTIONS:

Honda Gold Wing GL1800 2001-2017 Passenger Backrest Cover

| | |
|----------------------|-----------------------|
| Hardware: | Stock backrest screws |
| Tools needed: | Phillips screwdriver |

Removal of stock backrest:

1. Open Tour-Pak and remove the two backrest mounting screws.
2. Close the Tour-Pak. Lift the backrest up and off. If heated, disconnect the power cable.



Installation of Mustang backrest cover:

1. Slide the cover on top of the backrest aligning the center of the cover with the center of the backrest.
2. Bend in the side bolsters one at a time to get the backrest inside the cover.
3. Pull the bottom flap up and pull tight to remove any wrinkles, and then connect the hook-and-loop fastener. (Fig. 2)
4. Reinstall the backrest by re-connecting the power cable if heated and then sliding the top tabs into place. Insert the screws removed earlier through the trunk panel and secure the backrest into place by tightening the screws.



Enjoy the comfort and custom look of your new Mustang cover!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part number: 77781

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.