



MOUNTING SUGGESTIONS:

Honda VLX600 Shadow Tank Bib

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle, remove the fuel cap, and remove the 8mm bolt at the front of the fuel tank.
2. Lay the bib on the fuel tank and secure the front of the bib with the 8mm bolt.
3. Replace the fuel cap.
4. Remove the 12mm bolt at the base of the fuel tank and use it to secure the bottom of the bib.
5. Re-install the seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93127, 93128

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.