



## MOUNTING SUGGESTIONS:

### Honda VTX1300/1800 C/Retro/S/T/N Tank Bib

#### Installation of Mustang tank bib:

1. Remove the seat from the motorcycle, remove the fuel cap, and remove the three 5mm Allen bolts from the bottom of the dash.
2. Lift the dash and position the bib around the fuel cap hole and dash mounts.
3. Position the dash in place, and re-install the three 5mm Allen screws and the fuel cap.
4. VTX1300 Retro, S and T: remove the 8mm bolt and washer from the base of the tank and mount the bib to the base of the tank. The washer must be on top of the bib. (See page 2.)
5. Other models: Fasten the base of the bib to the frame using the provided ties.
6. Re-install the seat.

93321 pictured



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93169, 93170, 93175, 93176, 93179, 93180, 93302, 93303, 93320, 93321, 93344, 93345

**You are cordially invited to**  
**— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.