



MOUNTING SUGGESTIONS:

Honda VTX1800F Tank Bib

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle, remove the fuel cap, and remove the three 5mm Allen bolts from the bottom of the dash.
2. Lift the dash and position the bib around the lowest dash mount.
3. Hook the elastic strap around the base of the fuel tank mounting flange.
4. Position the dash in place, and re-install one 5mm Allen screws into the lowest mount, keeping pressure on the dash so the bib does not slide down.
5. Once the bottom mount is tight, reinstall the other two screws, the fuel cap and the seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93199, 93200

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.