



MOUNTING SUGGESTIONS:

Honda Valkyrie 1997-2003 & Interstate 1999-2001- Tank Bib

Installation of Mustang tank bib:

1. Insert the ignition key into the lock on left side cover and turn to unlock the seat. Remove the front seat.

2. Unlock the fuel cap and remove the two screws. Be sure not to drop them into the fuel tank. Lift off the fuel cap and chrome dash panel.

3. Remove the two tank bolts from the front and rear of the tank. Retain the bolt plug at the rear of the tank.

4. Push the bolt plug through the opening at the lower end of the tank bib.

5. Position the bib onto the tank and secure it with the two tank bolts.

6. Reposition the chrome dash panel, attach it and the fuel cap over the bib with the two stock screws, and reinstall the seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93129, 93130, 93153, 93154

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.