



MOUNTING SUGGESTIONS:

Kawasaki Vulcan 2000 Classic/LT Tank Bib

Installation of Mustang tank bib:

1. Remove the seat, then remove the dash mounting Allen bolt with a 4mm Allen wrench.
2. Open the fuel cap, then slide the dash back (toward the rear of the bike).
3. Position the tank bib over the fuel cap and the mounting boss.
4. Slide the dash forward into the front mounts and re-install the Allen bolt.
5. Remove the bolt and washer at the base of the tank with a 12mm wrench. With the washer on the bolt, push the bolt through the bib's lower mounting hole, and re-install into the tank and frame securely.
6. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93185, 93186, 93213, 93214, 93334, 93325

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.