



MOUNTING SUGGESTIONS:

Kawasaki Vulcan 900 Tank Bib

Installation of Mustang tank bib:

1. Remove the seat, then remove the 6mm dash bolt using a 4mm Allen wrench.
2. Lift the rear of the dash about an inch, then push it forward to disengage from the mounting pins.
3. Position the tank bib cutout around the speedometer, then under the front mounting pins. Pull the bib back until the rear of the cutout is over the dash mounting hole.
4. Align the front of the dash with the tank's mounting pins, slide back until the mounting hole lines up with the hole on the tank, and secure with the 6mm Allen bolt.
5. Remove the two tank mounting bolts at the base of the tank with a 12mm wrench and re-install them through the holes in the bib. Tighten securely.
6. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93197, 93198, 93306, 93307

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.