



MOUNTING SUGGESTIONS:

Yamaha Roadliner & Stratoliner '06-15 Solo Seat

Tools needed: 10mm socket wrench

Removal of Stock Seat:

1. Insert the ignition key into the left side cover and turn it counter-clockwise to unlock the front bracket. Lift solo's nose a few inches, then slide the seat forward and off the motorcycle.



2. Using a 10mm socket wrench, remove the two bolts from under the passenger seat.



3. Lift the front of the passenger seat and slide forward to remove the solo seat.

Installation of Mustang solo seat:

Note: If you are using both a solo and a passenger seat, the passenger seat must be installed before the solo.

1. Ensure the tool bag under the seat is not overstuffed and is positioned as low into the frame as possible.
2. Engage the Mustang solo seat's rear bracket into the fender mounting bracket. Push the solo as far back as possible.



3. Align the nose bracket with the frame receiver and push down until a click is heard, signifying the solo is latched into position. Ensure this bracket is firmly engaged before riding.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76122, 76124, 79452, 79454

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.