



MOUNTING SUGGESTIONS:

Triumph Speedmaster & America

2002-2008 - Solo and Passenger Seat

Hardware:	Solo seat: Chrome rear mounting bracket 10-32 x 5/8" screw x 2 Black retaining clip x 2 8mm x 15mm chrome buttonhead screw White nylon washer	Passenger seat: Stock rear fender screw 1/4"-20 x 3/4" Phillips screw x 2
Tools needed:	3mm Allen wrench 5mm Allen wrench 8mm wrench Phillips screwdriver	

Removal of Stock Seat:

1. Remove the rear fender screw with a 5mm Allen wrench and set aside. This screw will be used to mount the Mustang passenger seat.



2. Locate the pull ring on the left side of the seat and pull it to release the seat from the fender bracket.



3. Lift the seat up and back to remove from motorcycle.

4. Remove the fender bracket (including nut, bolts and washers) from the fender using a 3mm Allen wrench and an 8mm wrench. Insert the black retaining clips into the two outermost holes in the fender.



Installation of Mustang Seat:

Solo only:

1. Attach the chrome bracket to the rear of the solo using the provided 10-32 x 5/8" Phillips screws. (See photo on page 1.) Tighten securely, but do not overtighten.
2. Insert nose tab into the frame mount under the tank.
3. Position the white nylon washer between the rear solo bracket and the center fender hole and attach with the provided 8mm x 15mm screw. Tighten securely with a 5mm Allen wrench.



Solo and passenger seat:

1. Install the 8mm x 15mm screw provided with the solo into the open fender hole to prevent splash-through from the rear tire.
2. Attach the front brackets on the rear seat to the rear of the solo with the provided 1/4"-20 x 3/4" Phillips screws. Tighten securely, but do not overtighten. **Do not use the chrome solo bracket when installing with the passenger seat.**



3. Insert nose tab into the frame mount under the tank.
4. Position the white nylon washer between the rear passenger bracket and the rear fender hole and attach with the stock rear fender screw. Tighten securely with a 5mm Allen wrench.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76010, 76011, 76015, 76016, 76017, 76018, 79000, 79001, 79002, 79003, 79004, 79005

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.