



MOUNTING SUGGESTIONS:

Yamaha Bolt 2014-2018 Tank Bib

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle, and remove the fuel cap from the tank.
2. Position the tank bib on the fuel tank around the fuel hole. Replace the cap to hold the bib in position.
3. Pull the elastic cord around both sides of, and under, the bottom edges of the tank. The elastic cords should be threaded through the two loops at the base of the bib and knotted, and will be hidden from view.
4. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93225, 93226

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.