



MOUNTING SUGGESTIONS:

Yamaha Venture 1999-2011 Tank Bib

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle, and remove the fuel cap from the tank.
2. Remove the two screws from the dash panel and remove the dash panel.
3. Position the tank bib on the fuel tank over fuel hole and the two dash panel mounts.



4. Re-install the dash and tighten both screws. Replace fuel cap.
5. Remove the tank mounting bolt at the base of the fuel tank. Put the rubber washer onto the bolt, then push the bolt through the mounting hole at the base of the tank bib and tighten.
6. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93215, 93216, 93346, 93347

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.